

Output Filter Capacitors / Low Impedance						
SMD						
Series	Supplier	Voltage (Vdc)	Capacitance (µF)	Temp. (degC)	Lifetime (hrs)	Feature
TXV	Rubycon	10~35	10~470	-40~+125	2.000	125°C, Low Impedance
TZV	Rubycon	6.3~50	4.7~1000	-55~+105	2.000	Low Impedance
TFV	Rubycon	6.3~35	6.8~820	-55~+105	2.000	Low Impedance
JZV	Rubycon	6.3~35	4.7~1000	-55~+105	2.000	Low Impedance, higher soldering temp.
CE-GA	Sanyo	6.3~63	0.47~100	-55~+105	1.000	Low Impedance, max.height 5,4mm
CE-AX	Sanyo	6.3~50	4.7~50	-55~+105	1.000~2.000	Low Impedance
CE-KX	Sanyo	6.3~100	4.7~6800	-55~+105	1.000~2.000	Low Impedance
CE-LX	Sanyo	6.3~50	4.7~6800	-55~+105	2.000~5.000	Low Impedance, Long Life
CE-LL	Sanyo	6,3~50	10~1000	-25~+105	7.000~10.000	Low Impedance, Very Long Life
CE-PH	Sanyo	16~35	160~1500	-40~+125	2.000	125°C, Low Impedance
HVH	Sanyo	25~100	2.7~270	-55~+105	5.000~10.000	Hybrid Semiconductor Type, Super Low ESR
HVP	Sanyo	25~63	3.9~270	-55~+105	1.500~3.000	125°C, Hybrid Semiconductor Type
RADIAL						
Series	Supplier	Voltage (Vdc)	Capacitance (µF)	Temp. (degC)	Lifetime (hrs)	Feature
YXF	Rubycon	6.3~250	0.47~15000	-40~+105	2.000~10.000	Long Life, Low Impedance
YXG	Rubycon	6.3~100	6.8~18000	-40~+105	3.000~6.000	High Ripple Current
YXH	Rubycon	6.3~100	6.8~18000	-40~+105	4.000~10.000	High Ripple Current, Long Life
ZL	Rubycon	6.3~100	5.6~6800	-40~+105	1.000~5.000	High Ripple Current, Low Impedance
ZLH	Rubycon	6.3~100	8.2~8200	-40~+105	6.000~10.000	Miniaturized, Long Life, Low Impedance
ZLG	Rubycon	6.3~35	4.7~3900	-40~+105	1.000~5.000	Ultra Low Impedance
ZLJ	Rubycon	10~50	27~2200	-40~+105	7.000~10.000	Miniaturized, Long Life, Ultra High Ripple
ZT	Rubycon	6.3~35	22~2200	-40~+125	1.000~4.000	125°C, Low Impedance
RX30	Rubycon	10~100	1~4700	-40~+130	2.000~4.000	130°C, Low Impedance